



Moneysworth & Best  
120 Midair Court  
Brampton, ON, L6T 5V1  
Canada  
905-790-0650

**PRODUCT: Moneysworth & Best Pro-Tex - 300g**

**CODE: 086100**

### SECTION 01: IDENTIFICATION

Product Identity.....Moneysworth & Best Pro-Tex - 300g  
Product Item Numbers.....086100  
Manufacturer.....Moneysworth & Best  
120 Midair Court  
Brampton  
Ontario  
Canada  
L6T 5V1  
905-790-0650  
24 hour emergency telephone number.....CANUTEC: 1-613-996-6666.  
Recommended Use.....Lubricates leather and protects against drying and deterioration .  
Consumer Commodity.....Yes.

### SECTION 02: HAZARD IDENTIFICATION

Emergency Overview..... Danger. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. May catch fire. Do not puncture. Do not burn. May irritate eyes and skin. Harmful or fatal if swallowed.

Potential Health Effects:  
Eye Contact..... This product causes irritation, redness and pain.  
Skin Contact ..... Can cause skin irritation. Prolonged or repeated contact may dry the skin.  
Ingestion..... Harmful if swallowed.  
Inhalation..... Can cause headaches, dizziness, fatigue, lack of coordination, tremors and unconsciousness.

### SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Heptane	142-82-5	60-100
Propane	74-98-6	10-30

### SECTION 04: FIRST-AID MEASURES

Eye Contact.....Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.  
Skin Contact.....Remove contaminated clothing. Wash thoroughly with soap and lukewarm water. If irritation or redness develops, seek medical attention.  
Ingestion.....If swallowed, get medical attention immediately. Do not induce vomiting .  
Inhalation.....Move victim to fresh air. If breathing has stopped, give artificial respiration. If heartbeat absent, give external cardiac compression. Monitor breathing and pulse. If symptoms persist, call a physician.  
Additional Information.....Note to the doctor; treat symptomatically.

### SECTION 05: FIRE-FIGHTING MEASURES

Flammability Class..... Extremely Flammable.  
Conditions..... Excessive heat, sparks and open flame.  
Fire and Explosion Hazards..... May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products. Thermal decomposition products are toxic and may include carbonyl halides, Hydrofluoric Acid and oxides of carbon.  
Extinguishing Media..... Wear NIOSH approved self-contained breathing apparatus or equivalent and full protective gear. Use water spray to cool fire-exposed containers in order to prevent pressure build up.  
Sensitivity to Mechanical Impact..... Not expected to be sensitive.  
Sensitivity to Static Discharge..... Not expected to be sensitive.

### SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective ..... No action shall be taken involving any personal risk or without suitable training. Evacuate Equipment and Emergency Procedures surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

**PRODUCT: Moneysworth & Best Pro-Tex - 300g**

**CODE: 086100**

**SECTION 06: ACCIDENTAL RELEASE MEASURES**

Emergency Procedures..... Spilled product is flammable. Ensure that all sources of ignition are eliminated near the spilled material. Wipe up with a damp cloth. Rinse the cloth thoroughly and allow to dry before laundering.

Environmental Precautions..... Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods and Materials for Containment .. and Cleaning Up .. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13).

**SECTION 07: HANDLING AND STORAGE**

Precautions for Safe Handling.....Do not breathe vapour or mist. Avoid contact with eyes, skin, and clothing. Smoking, eating and drinking should be prohibited in the application area. Keep away from heat, sparks, and open flames. Do not puncture, burn or incinerate. Do not place near sources of heat. Keep from freezing.

Conditions for Safe Storage including any Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Keep container tightly closed in a dry, cool and well-ventilated place. Do not store in temperatures above 120°F (50°C). Store away from incompatible materials. Do not puncture or incinerate. KEEP OUT OF REACH OF CHILDREN.

Incompatibilities .....Segregate storage away from materials indicated in Section 10.

**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	OSHA PEL		NIOSH REL
			PEL	STEL	
Heptane	400 ppm	500 ppm	500 ppm	Not available	85 ppm for n-Heptane, 440 ppm for a ceiling conc. Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Eye/Face Protection.....	Do not get in eyes. Wear safety glasses with side-shields.				
Skin Protection.....	Normally, no hand protection is required; however, prolonged or repeated contact with skin use chemical resistant gloves conforming to appropriate regulations. Observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.				
Respiratory Protection.....	Avoid breathing dust/fume/gas/mist/vapors/spray. If permissible levels are exceeded use NIOSH mechanical filter/organic vapor cartridge or an air-supplier.				
Appropriate Engineering Controls.....	Good general ventilation should be used. Ventilation rates should be matched to conditions. Use local exhaust ventilation to maintain airborne levels below the Threshold Limit Value.				
Exposure Limits					

**SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Physical State.....Aerosol.

Physical Appearance.....Clear mist.

Odour.....Hydrocarbons.

Odour Threshold (ppm).....Not available.

pH.....Not applicable.

Internal can pressure @21C (psig) .....50-60.

Vapour Density (Air=1).....>1.

Evaporation Rate (n-Butyl Acetate = 1).....> 1 (n-Butyl Acetate = 1).

Initial Boiling Point/Boiling Range (°C).....98 °C ( 209°F).

VOC Content.....None.

Specific Gravity (Liquid).....0.710-0.770 @ 25°C.

Specific Gravity (Aerosol).....0.680 - 0.720.

Solubility in water.....Nil.

Aerosol Flame Projection.....> 45 cm but < 100 cm. Auto

Ignition Temperature (Propellant), °C470.85 °C (888.5 °F) .

Flashback.....Yes.

Flash Point (°C), Method.....-104 °C (-156°F).

Lower Explosive Limit (% , vol).....2.1.

Upper Explosive Limit (% , vol).....9.5.

**PRODUCT: Moneysworth & Best Pro-Tex - 300g****CODE: 086100****SECTION 10: STABILITY AND REACTIVITY**

Reactivity .....Product not reactive under normal conditions of use.  
 Chemical Stability.....Stable under the recommended storage and handling conditions.  
 Possibility of Hazardous Reactions.....Will not occur.  
 Conditions to Avoid.....Avoid sources of heat and flame, and electrostatic charge.  
 Incompatible Materials.....Strong oxidizing agents.  
 Hazardous Decomposition Products.....May form carbon dioxide and carbon monoxide, various hydrocarbons.

**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Heptane	23.3 mg/L (Rat - 4hrs)	>5,840 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rat)
Propane	658 mg/L (Rat - 4 hrs)	Not available
Route of Exposure.....	Skin contact, Eye contact, Inhalation.	
Effects of Acute Exposure.....	High vapor/aerosol concentrations may be irritating to eyes. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping. In high concentrations, vapors and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Ingestion may result in vomiting.	
Chronic Effects.....	Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Prolong contact may defat and dry the skin, leading to discomfort and dermatitis .	
Carcinogenicity.....	Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP.	
Reproductive Toxicity.....	No information is available, and no adverse effects are expected.	
Teratogenicity.....	No information is available, and no adverse effects are expected.	
Germ Cell Mutagenicity.....	No information is available, and no adverse effects are expected.	
Toxicological Data		

**SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity..... Heptane (CAS#:142-82-5): Toxicity to fish: LC50 1.284 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 0.1 mg/L, 96 hrs; Toxicity to algae: EL50 4.338 mg/L, 72 hrs.  
 Persistence and degradability ..... Heptane: Readily biodegradable.  
 Bioaccumulation Potential..... Not available.  
 Other Adverse Effects..... Very toxic to aquatic life with long lasting effects.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

**SECTION 14: TRANSPORT INFORMATION**

TDG (Canada- Road)..... AEROSOLS, Class 2.1, UN1950.  
 DOT (US-Road)..... AEROSOLS, Class 2.1, UN1950, LTD QTY, Consumer commodity ORM-D.  
 IMDG (International- Marine)..... AEROSOLS, Class 2.1, UN1950.  
 IATA (International- Air)..... AEROSOLS, Class 2.1, UN1950, LTD QTY.

**SECTION 15: REGULATORY INFORMATION**

Canada Regulations:.....WHMIS Classification. B5: Flammable aerosol. D2B: Material causing other toxic Materials. US Regulations.....Environmental Protection Act: Constituents of this product are included on the TSCA inventory. OSHA (29CFR 1910.1200) Classification: Compressed Gas. HIMS Classifications: see section 01.

**SECTION 16: OTHER INFORMATION**

HMIS..... Health: 2 Fire: 4 Reactivity: 0 PPE: B.  
 NFPA..... Health: 2 Fire: 4 Reactivity: 0 Special: -.  
 Disclaimer..... The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Empack assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. THIS SDS IS VALID FOR THREE YEARS.

